

3D Shaker TRDS-601

3D Shaker TRDS-601

www.axylab.com | info@axylab.com

Overview

3D Shaker TRDS-601 is accessible with a variety of brackets and fixtures. It has a dual LCD screen that displays the time and speed separately. A DC motor with a maximum speed of 10 to 80 rpm and a working temperature of 5 to 40 °C. Controls the mechanism. It can be used with a timer or in continuous operation mode. It is capable of supporting a maximum load weight.

Features:

- - The mechanism is performed by a DC motor control
 - It has a maximum load-bearing weight capability
 - Presented with a double LCD screen, it shows display time and speeds separately
 - Making an available variety of brackets and fixtures are available
 - It can be used with a timer or in continuous operation mode
 - The mechanism is controlled by a DC motor control

Applications:

- Making an available variety of brackets and fixtures are available
- It can be used with a timer or in continuous operation mode
- The mechanism is controlled by a DC motor control

Specifications :

Angle of Inclination	7°
Data Access	None
Dimension (L×W×H)	335×270×140 mm
Maximum Load	3kg
Moisture	0.8
Motor Type	DC motor
Operation Model	Time set, continuous operation
Power	20W
Speed Indicator	LCD
Speed Range	10 to 80rpm
Time Range	1 min to 19h59min
Timer Indicator	LCD
Voltage	100 to 240V, 50/60Hz
Weight	3.2kg
Working Temperature	5 to 40°



Northeast McClain Road Bentonville AR 72712, USA
Email: info@axylab.com | Website: www.axylab.com