



## **3D Shaker TRDS-602**

[www.axylab.com](http://www.axylab.com) | [info@axylab.com](mailto:info@axylab.com)

## Overview

3D Shaker TRDS-602 is manageable with a variety of supports and fittings. It has a dual LCD screen that displays the time and speed separately. A DC motor with a maximum speed of 10 to 70 rpm and a working temperature of 5 to 40 °C. Controls the mechanism. It can be used with a timer or in continuous operation mode. It is accomplished by supporting an extremely heavy.

## Features:

- The mechanism is performed by a DC motor control
- It has a maximum load-bearing weight capability
- Presented with a double LCD screen, it shows display time and speeds separately
- Making an available variety of brackets and fixtures are available
- It can be used with a timer or in continuous operation mode
- The mechanism is controlled by a DC motor control

## Specifications :

<b>Angle of Inclination</b>	10°
<b>Data Access</b>	RS232
<b>Dimension (L×W×H)</b>	425×355×180mm
<b>Maximum Load</b>	5kg
<b>Moisture</b>	0.8
<b>Motor Type</b>	DC motor
<b>Operation Model</b>	Time set, continuous operation
<b>Power</b>	50W
<b>Speed Indicator</b>	LCD
<b>Speed Range</b>	10 to 70rpm
<b>Time Range</b>	1 min to 19h59min
<b>Timer Indicator</b>	LCD
<b>Voltage</b>	100 to 240V, 50/60Hz
<b>Weight</b>	9kg
<b>Working Temperature</b>	5 to 40°,



Northeast McClain Road Bentonville AR 72712, USA  
Email: [info@axylab.com](mailto:info@axylab.com) | Website: [www.axylab.com](http://www.axylab.com)