



## Constant Temperature Metal Bath TRCM-601

[www.axylab.com](http://www.axylab.com) | [info@axylab.com](mailto:info@axylab.com)



## Overview

Constant Temperature Metal Bath TRCM-601 uses a simpler and more convenient temperature correction method. It can transport a wide range of modules. It has a programming number of 9 and operates at a temperature range of 5 to 40 °C. It has a patented module clamping, pressing method, and a temperature control range of 5 to 110 °C. It has an LCD screen with a touch keyboard for placing and operating parameters, and it is designed to be used in a metal bath. It can cool as well as heat.

## Features:

- The temperature adjustment range of 15 to 110 °C is excellent
- The maximum temperature accuracy is 0.5 °C
- It can transport a variety of modules
- Assist in the editing and storage of programs
- The temperature correction method is more straightforward and convenient
- The patented technique of clamping and pressing modules
- It Can be used for both cooling and heating



## Specifications :

<b>Dimensions L×W×H</b>	186×267×145 mm
<b>Display</b>	LCD
<b>Input Voltage</b>	100 to 120V/220 to 240V, 50Hz/60Hz
<b>Maximum Cooling Rate</b>	5 °/min
<b>Maximum Heating Rate</b>	5.5 °/min
<b>Power</b>	180 W
<b>Programming</b>	9
<b>Temperature Control Accuracy 20 To 45 °</b>	± 0.5 °
<b>Temperature Control Range</b>	lowest is 25 °, highest is 110 °
<b>Temperature Range</b>	-5 ° / 110 °
<b>Temperature Uniformity 20 To 45 °</b>	± 0.5 °
<b>Time Setting Range</b>	1min to 99 h 59 min
<b>Working Environment Humidity</b>	0.8
<b>Working Environment Temperature</b>	5 to 40 °



Northeast McClain Road Bentonville AR 72712, USA  
Email: [info@axylab.com](mailto:info@axylab.com) | Website: [www.axylab.com](http://www.axylab.com)