



## Flame Photometer TRFP-603

[www.axylab.com](http://www.axylab.com) | [info@axylab.com](mailto:info@axylab.com)

## Overview

Flame Photometer TRFP-603 is equipped with a 7-inch LCD touch screen and having with a programmed calculation of the correlation coefficient. It has the ability of simultaneous measurement of the elements Na, K, Ca, Ba, and Li. It is a flameout protection device and comes with an air compressor. It has a compassion range of elements. In addition, the repeatability of elements is 1% CV for 20 consecutive samples and can accept the sample 6L/min.

## Features:

- It has a 7-inch LCD touch-screen
- Consistent, simultaneous measurement of elements
- It can automatically calculate the coefficient correlation
- Flameout protection device
- LPG is a flammable gas
- Information of direct concentration
- Flame size pre-selection
- Range shifts were quantified
- The device contains an air compressor

## Specifications :

<b>Gross Weight</b>	17 kg
<b>Linearity</b>	0.195ppm?0.39 to 3.12?ppm, 0.69ppm?1.15 to 9.2?ppm, 0.15ppm?0.25 to 5?ppm
<b>Package</b>	570×530×380mm 0.115M3
<b>Range</b>	0 to 100 ppm
<b>Repeatability</b>	1 % CV for 20 consecutive samples
<b>Respond time</b>	8s
<b>Sample uptake</b>	6L/min
<b>Sensitivity</b>	0.1ppm



Northeast McClain Road Bentonville AR 72712, USA  
Email: [info@axylab.com](mailto:info@axylab.com) | Website: [www.axylab.com](http://www.axylab.com)